



Generator Specifications

KP SERIES

KP- C28P

50 Hz @ 1500rpm, 415V

STANDARDS

Manufacturing Standards

- Manufactured strictly according to ISO9001-2008
- CE certified

General Features

- Deepsea controller DSE6120 digital controller.
- 50°C tropical radiator
- Varta brand maintenance-free starter batteries
- ABB 4 pole circuit breaker as standard
- Anti-vibration mountings between engine/ alternator and base frame.
- Industrial silencer with connecting flange.
- Bunded fuel tank
- With side bumpers.

Engine Data

- Engine Brand Cummins
- Engine Model 4B3.9-G2
- Cylinders 4 in-line
- Induction Naturally Aspirated
- Compression Ratio 18.0:1
- Displacement 3.9L
- Alternator 63A
- Oil Capacity min 10.9 litres

Alternator Data

- Alternator Brand LeRoy Somer
- Alternator Model TAL-A42-C
- Insulation class H
- Excitation Shunt
- Protection IP23
- Frequency (Hz) 50
- Voltage Reg ±1%
- Winding 2/3 pitch
- AVR model R120

Factory testing

- Gensets filled with coolant to test at 25%, 50%, 75%, 100% and 110% load prior to shipment.

Technical Data

- Model KP-C28P
- Tank Capacity 250L
- Dry Weight 1321Kg
- Dimensions 2602 L x 1100 W x 1506 H
- Prime power 28kVA 22kw
- Noise Level 75dB @ 7m
- Ambient temperature capability 40 degC
- Fuel Consumption l/hr 6.7
- Altitude capability <1000m

Keypower reserves the right to make changes to technical specification, colour, configuration and accessories without prior notice. Please confirm with salesperson before placing order.

